

PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Spectrum Technologies N.A. Inc.

12245 Wormer Ave, Redford, MI 48239

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Mechanical and Thermodynamic Testing (As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szuszen

Tracy Szerszen President

Perry Johnson Laboratory Accreditation, Inc. (PJLA) 755 W. Big Beaver, Suite 1325 Troy, Michigan 48084 Initial Accreditation Date:Issue Date:Expiration Date:April 26, 2015August 16, 2023November 30, 2025Accreditation No.:Certificate No.:82464L23-616

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: <u>www.pjlabs.com</u>



Certificate of Accreditation: Supplement

Spectrum Technologies N.A. Inc.

12245 Wormer Ave, Redford, MI 48239 Contact Name: Michael Pickel Phone: 313-387-3000

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Thermodynamic ^F	Medical Components,	Temperature	GM, Ford, Chrysler	-40 °C to 150 °C
	Automotive Components and		and Other Customer	
	Products, Mechanical		Specifications, MIL	
	Products, Electrical and		STD 810 (in	
	Electronic Components and		conjunction with	
	Products		vibration and	
			mechanical shock)	
Mechanical F		Vibration	GM, Ford, Chrysler	5 Hz to 2 000 Hz
			and Other Customer	
			Specifications, MIL	
			STD 810	
		Mechanical Shock	MIL STD 810	1 g to 100 g
			Customer Specification	6 ms to 25 ms
		Shipping Simulation	MIL STD 810	Vibrations:
		Material Handling	ASTM D4169	5 Hz to 2 000 Hz
			Customer Specification	Shock:
				1 g to 25 g
				6 ms to 25 ms

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this testing at its fixed location.